CATALOGUE

TABLE OF CONTENTS

SECTION	PAGES	COLOR
Head and Face Protection	1-8	COLOR
Eyewear Protection	9-13	
Hearing Protection	14-24	
Respiratory Protection	25-33	
Hand Protection	34-39	
Aluminize Wear	40-42	
	43-44	
Traffic Safety	45-46	
Foot Wear (King's Safety Shoes) Fall Protection		
	47-57	
Body Protection	58-60	
Salisbury	61-62	
Wisdom	63-64	
Zoll (Medical)	65-69	
Honeywell Fenzy/ Fire Rescue	70-72	
Eye wash	73-74	
Flexovit /Bahco/Norton/Toka	75-78	
Adhesives & Abrasives:	79	
Crocodile Masking Tape		
Crocodile Electrical Tape		
Crocodile Aluminum Duct Crocodile Aluminum Duct		
Crocodile SandpaperCrocodile Floor Sanding Grit		
3M Floor Sanding Grit		
Britannia Teflon Tape		
WD 40	80	
Spray Paint:		
Jackson Electrical Contact Cleaner		
Bosny Spray Paint		
Paint Rollers & Brush:		
Hitech Baby Foam Roller		
(Refill, Radiator)		
Globe Paint Brush		
Drill Bit	81	
Other New Items:	82-87	
Impact Sport Electronic Earmuffs		
Honeywell Anti-Cut Gloves Salishury Cloves		
Salisbury GlovesEmergency Eyewash Shower Type		
Rain boots (Camel Ordinary &		
Supertuff Rainboots with Steel Toe)		
ZOLL M Series		
Zoll Ventilator Eagle II		
Silicon Sealant		
Crocodile Cloth duct tape		
PHILLYX BILL FOR WILDING SKINGS Adela Honeywell FENZY FLEX OVIE ALL TOWNED FOR WILDING WILDING WILDING		
WD-40 ZOLL NORTH HOWARD TOKA NORTH LEGHT TOKA NORTH		
MORNING PRIDE It's about time.		















































3rd Edition 2019- RAC

Serial No. _____



Blue Eagle HC32 Safety Helmet



Model Number: HC32

Colors: White, Blue, Yellow, Green, Orange

Comes with: Liner, Chin Strap

Materials: ABS

Specification: Electrical Insulation, 6-point Suspension

provides better impact resistance, complied with CE, Made in

Taiwan.

Blue Eagle M1 Helmet Chin Strap



Model Number: M1

Color: Green

Specification: To prevent from hanging user's and causing injury, chin straps would be broken under a force between

150-250N, Compiled with CEEN397, Made in Taiwan

 $C \in$

CE

Blue Eagle M2 Cap Suspension



Model Number: M2

Color: White

Specification: Pin-Lock, 6-point Polyethylene suspension

Blue Eagle SU3R Cap Suspension



Model Number: SU3R

Specification: Ratchet, 6-point nylon Suspension, used with

HR36 Safety Cap, compiled with CE EN397

((



Blue Eagle A2 Visor Bracket



Model Number: A2

Color: Black Material: ABS

Specification: Fit in with regular safety helmets, Used with

"FC" series visors, Complied with CE EN166, ANSI Z87 (ANSI Z87



Blue Eagle A3 Visor Bracket



Model Number: A3

Color: Black

Material: ABS/Aluminum Material

Specification: Fit in with regular safety helmets, Used with

"FC" series visors, Complied with CE EN166, ANSI Z87 (E (ANSI



Blue Eagle HG1 Head Gear



Model Number: HG1

Color: Black

Material: Polypropylene Adjustment: Ratchet

Specification: Use for welding helmets and faceshield.

Blue Eagle HR82 Slotted Helmet



Model Number: HR82

Color: Red, White, Blue, Yellow, Green, Orange Suspension: Rachet, 6-point nylon suspension

Specification: Eletrical insulation, 6-point suspension provides better impact resistance, complied with ANSI Z89.1 (ANSI



Blue Eagle BP65 Bump Cap



Model Number: BP65

Color: Yellow, Red, Blue, White, Orange, Green

Material: Polyethylene

Suspension: 4-point PE suspension

Specification: The Bump cap is intended to protect the wearer's head against injury caused by striking the head against hard, stationary objects, DO NOT use a bump cap in environment where an Industrial Safety Helmet is required. CE EN812

Blue Eagle M6 Cap Suspension Bump Cap



Model Number: M6

Color: White

Specification: Pin-lock, 4-point polyethylene Suspension, used

with BP65 Bump Cap, compiled with CE EN397





Blue Eagle 633P Welding Helmet



Color: Black Model Number: 633P

Lens Size: 4.25 x 2 or 108 x 51 mm Material: Polypropylene Specification: Lift front lens holder, thoughness and moisture

proof. Complied with CE, ANSI Z87, CSA Z94.3





Blue Eagle 632P Welding Helmet (Hand Shield)



Model Number: 632P Color: Black

Lens Size: 4.25 x 2 or 108 x 51 mm Material: Polypropylene

Large Viewing Area: 4.25 x 2

Specification: Thoughness and moisture proof. Complied with CE



Blue Eagle 633N Welding Helmet Nylon Type



Model Number: 633N Color: Black **Lens Size**: 4.25 x 2 or 108 x 51 mm Material: Nylon

Specification: Lift front lens holder, thoughness and moisture

proof. Complied with ANSI



Blue Eagle 6PA3 Welding



Model Number: 6PA3 Color: Black

Lens Size: 4.25 x 2 or 108 x 51 mm Material: Propylene Specification: Lift front lens holder, clip cap welding helmet, Aluminum bracket, moisture proof. Complied with ANSI Z87



Blue Eagle 633N Welding Helmet Nylon Type



Model Number: 633N

Size of Filter: 110x90x9mm/ 133x114x9mm

View Area: 90x 40/ 97x60mm Power Supply: Lithium Solar Cells (

Working Temperature: -5°C (23°F) to 55°C (131°F)

Shade Number in Light State: Din4#, Dark state: Din9 13#

Response Time: <0.1ms Room temperature

Return Time: Rapid 0.2s Slow 0.8s



Blue Eagle NP312 Chemical Hood




Model Number: NP312

Specification: The Assembly consists of a twin cartridge respirator and a light weight hood, designed to protect head, face, eyes and lungs against dust, paints, solvent, etc PC lenses x 2 PCS

(5.5x110x200mm)

Blue Eagle NP901 Arc-Welding Leather Hood



Model Number: NP901

Total Length x Width: 480mm x 650mm

Specification: Lift front lens holder, used in narrow working areas

for arc-welding operation

Blue Eagle NP503 Air-Supplied Sandblast Hood



Model Number: NP503

Color: PVC and Nylon Fabric Cloth

Outer Lens: Heat Treated Glass: 114x133x5mm **Inner Lens:** Polycarbonate (PC): 114x133x1mm

Safety Cap: Polyethylen

Specification: Designed for all sandblasting operations, air

regulator provides smooth and low noise air flow

Blue Eagle NP505 Air Supplied Spray Hood



Model Number: NP505

Specification: Light in weight, replaceable visor, air regulator

provides smooth and low noise air flow.



Blue Eagle B1YE Browguard



Model Number: B1YE

Colors: Blue, Yellow, Green, Orange Materials: High impact resistance ABS

Specification: Fit all FC series visors, made of high impact resistance ABS, provide the best protection, Large cover area for user's forehead, providing full protection, complied with

CE EN166, ANSI Z87, CSA Z94.3





Blue Eagle FC25 Face shield



Model Number: FC25 Colors: Clear

Materials: Polycarbonate Size: 8x 12" (203 x 304mm)

Thickness: 0.8mm

Specification: Provide protection against high-speed impact penetration, and splash of liquids, best optical quality (highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic power and light diffusion)

protective films both sides. Complied CE CSA





Blue Eagle FC28 Face Shield



Model Number: FC28 Colors: Clear Materials: Polycarbonate Size: 8"x12"

Thickness: 1.0mm

Specification: Aluminum bound, Use with "B" series Browguards, for high impact, penetration, splash and heat

resistance, complied CE ANSI CSA



Blue Eagle FC28G5 Faceshield



Color: Dark Green

Material: PolyCarbonate **Size:** 8 x 12" (203 x 304 mm)

Thickness: 1.0mm



Specification: Provide protections against high-speed impact (120 m/s), penetration, and splash of liquids, Professional UV filter, which filters out 99.9 % of UV rays. ANSI Z87+ Shade Number: U5, Best optical quality (highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion), Protective films on both sides. CE (ANSI)



Blue Eagle FC29 Faceshield



Model Number: FC29

Color: Black

Material: Steel Mesh Size: 8 x 12"

Specification: Steel wire mesh (more in heat-resistance), for

flying chips and splinters

Blue Eagle FC45 Faceshield



Model Number: FC45

Colors: Clear

Materials: PolyCarbonate Size: 8 x 15½" (203 x 393 mm)

Thickness: 0.8mm

Specification: : Provide protections against high-speed impact

(120 m/s), penetration, and splash of liquids,

Best optical quality (highest ranking at the tests of spherical

refractive power, astigmatic refractive

power, prismatic refractive power, and light diffusion), Protective films on both sides (prevent damages and scratches during transportation), Aluminum bound (faceshield can be bent/adjusted easily), Complied with CE EN166, CSA

Z94.3

Blue Eagle FC48 Faceshield



Model Number: FC48

Colors: Blue, Yellow, Green, Orange Materials: High impact resistance ABS

Specification: Fit all FC series visors, made of high impact resistance ABS, provide the best protection, Large cover area for user's forehead, providing full protection, complied with

CE EN166, ANSI Z87, CSA Z94.3



C € ∰





Blue Eagle FC83 Faceshield



Model Number: FC83

Color: Clear

Material: Polycarbonate Size: 8" x 15½" Thickness: 1.0mm Specification: Without Aluminum bound, Assembled with C3 chin guard and "B" series browguards, providing extra

protection

Blue Eagle K4YE Browguard



Model Number: K4YE

Colors: Blue, Yellow, Green, Orange Materials: High impact resistance ABS

Specification: Fit all FC series visors, made of high impact resistance ABS, provide the best protection, Large cover area for user's forehead, providing full protection, complied with

CE EN166, ANSI Z87, CSA Z94.3





Blue Eagle K25 Faceshield



Color: Clear

Material: Polycarbonate Size: 8 x 12" (203 x 304 mm)

Thickness: 0.8 mm

Specification: Provide protections against high-speed impact

(120 m/s), penetration, and splash of liquids,


Best optical quality (highest ranking at the tests of spherical

refractive power, astigmatic refractive

power, prismatic refractive power, and light diffusion),

Protective films on both sides, Complied with

CE EN166, CSA Z94.3





Model Number: C3YE

Color: Yellow, Blue, Orange, Gree Material: Impact Resistant ABS

Specification: Providing extra face protection, Assembled with FC73 or FC83 visors and "B" series browguards



Blue Eagle NP102 Safety Goggles



Model Number: NP102

Color: Clear

Material: Polycarbonate Thickness: 1.0mm

Specification: Provide protections against impact and dust, Best optical quality (highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion) Complied with CE

EN166, ANSI Z87

Blue Eagle NP103 Safety Goggles



Model Number: NP103

Color: Clear

Material: Cellulose Acetate Thickness: 1.0mm

Specification: Anti-Fog [CE Certified] for impact and dust,

Direct venting

 ϵ

C E (ANSI)

Blue Eagle NP104 Safety Goggles



Model Number: NP104

Color: Clear

Material: Polycarbonate Thickness: 1.0mm

Specification: Provide protections against impact and dust, Best optical quality (highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion) Complied with CE

EN166, ANSI Z87



Blue Eagle NP105 Safety Goggles



Model Number: NP105

Color: Clear

Material: Cellulose Acetate

Thickness: 1.0mm

Specification: Anti-fog (approved by CE standard), Indirect

valve, used for fog, fine dust, and chemical splash.



Eyewear Protection

Honeywell LG100A Safety Goggles



Model Number: LG100A Lens: Clear Polycarbonate

Frame: Clear PVC

Coating: Anti-scratch / Anti-Fog

Specification: Asian face design, Large area of "Shark Gill" air vent makes the goggle breath freely and more comfortable with long time wear, Indirect vent holes offer better safety and decrease the risk of chemical splash and particulates into eyes, Extended design of the nose pad leads to better comfort and fit, Widened head band with elastic nylon can reduce the pressure to head and maintains excellent flexibility & comfort for long term use, Can be worn over normal glasses as an OTG

Honeywell V-Maxx™ Safety Goggles



Model Number: V-Maxx™ Lens: Clear Polycarbonate Body: Indirect Ventilation

Headband: Elastic,

Coating: Anti-scratch / FogBan

Specification: Fits a wide variety of workers and can be worn over prescription eyewear and with half-mask respirators, Selection of various strap materials to ensure stability for all types of environments, (i.e. neoprene strap for use in chemical industry), Rotating strap attachments for easier use with hard hats, Special concept of indirect ventilation to comply with splash-resistance test, Lens options in polycarbonate or acetate, Lens protectors available to increse V-Maxx lifetime



Eyewear Protection

Blue Eagle SG154 Safety Goggles



Model Number: SG154

Color: Clear

Material: Polycarbonate Thickness: 1.5mm

Specification: Provide protections against high speed impact

(120 m/s) and dust, Best optical quality

(highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion), Complied with CE EN166, ANSI Z87

C E (ANSI)

Blue Eagle NP1063 Gas Welding Goggles



Model Number: NP1063

Color: Green

Material: Polycarbonate Thickness: 1.0mm

Specification: Provide protections against impact and dust, Professional UV filter, which filters out 99.9% of UV rays. ANSI

Z87 Shade Number: U3,

Best optical quality (highest ranking at the tests of spherical

refractive power, astigmatic refractive

power, prismatic refractive power, and light diffusion),

Complied with ANSI Z87



Blue Eagle GW250 Gas Welding Goggles



Model Number: GW250

Color: Dark Grey

Specification: Lift-front type lenses holder, Used for both of

welding and chipping operation



Eyewear Protection

Honeywell A700 Safety Spectacles



Model Number: A700 Lens: Clear Hard Coat

Frame: Clear **Coating**: FogBan / Anti-scratch **Specification**: Affordably priced sporty Styling, Lightweight design with sport temples and soft temple tip pads. Moulded universal nose bridge, 8-base polycarbonate abrasion resistant lenses, Secure wrap around lens design

Honeywell A700 Safety Spectacles



Model Number: A700 Lens: Grey TSR Hard Coat
Frame: Grey Polycarbonate Coating: Anti-scratch
Specification: Affordably priced sporty Styling, Lightweight
design with sport temples and soft temple tip pads.
Moulded universal nose bridge, 8-base polycarbonate
abrasion resistant lenses, Secure wrap around lens design

Honeywell A800 Safety Spectacles



Model Number: A800 Lens: Clear Hard Coat

Specification: Slim profile provides an ideal fit for workers with smaller faces. Sporty styling provides a fashionable fit, 9-base polycarbonate abrasion resistant lenses, provide a 180° field of distortion-free vision, temples feature soft and padded inserts with extra flex built inSoft nosepiece conforms to various nose bridge shapes Lightweight: 22 gr

Honeywell A800 Safety Spectacles



Model Number: A800 Lens: Grey TSR Hard Coat Frame: Grey Coating: Anti-scratch

Specification: Slim profile provides an ideal fit for workers with smaller faces. Sporty styling provides a fashionable fit, 9-base polycarbonate abrasion resistant lenses, provide a 180° field of distortion-free vision, temples feature soft and padded inserts with extra flex built in Soft nosepiece conforms to various nose bridge shapes Lightweight: 22 gr



Honeywell A800 Safety Spectacles



Model Number: A800 Lens: Silver **Coat Frame:** I/O Hard Coat Coating: Anti-scratch **Specification:** Slim profile provides an ideal fit for workers with smaller faces. Sporty styling provides a fashionable fit, 9base polycarbonate abrasion resistant lenses, provide a 180° field of distortion-free vision, temples feature soft and padded inserts with extra flex built in Soft nosepiece conforms to various nose bridge shapes Lightweight: 22 gr

Honeywell A900 Safety Spectacles




Model Number: A900 Lens: Grey TSR Hard Frame: Black Coating: Anti-scratch / FogBan Specification: Sporty, 8-base wrap-around polycarbonate lens, Non-slip ruber nose bridge, temples with soft, padded inserts provide a comfortable fit, Available with scratchresistand hardcoating, Dielectric frame, Complies with ANSI

Z87 + high impact standard




Honeywell VisiOTG-A Over-The-Glass-Spectacles



Frame: Clear

Coating: Anti-scratch / FogBan



standard





Blue Eagle NP353 Earplugs



Model Number: NP353

Material: PVC Color: Yellow

Specification: With Yellow plastic case, key chain & neck string Complied with CE SNR = 26dB and ANSI NRR = 23 dB



Blue Eagle NP363 Earplugs



Model Number: NP363


Material: TPR Color: Blue

Specification: Provide good noise attenuation and protect wearer's ears from loud noises, Reusable type, With blue plastic box and metal key chain, With neck string, CE SNR =

29dB and ANSI NRR = 25dB



Honeywell MAX® Earplugs



Model Number: Max-1

Color: Coral Style: Uncorded

NRR: 33

Material: Polyurethane Shape: Bell

Size: Universal

Packaging: PolyBag [200 per box]

Specification: The world's most-used polyurethane foam earplug, Bell shape delivers maximum in-ear comfort, Contoured design easier to insert, resists tendency to backout of ear canal, Polyurethane foam enhances comfort, especially for long-term wear, Smooth, soil-resistant closed cell-foam skin prevents dirt build-up, Bulk refills for Leight® Source 400 and Leight® Source 500 Earplug Dispensers save (ANSI

time, waste and space



Honeywell MAX® Earplugs



Model Number: Max-30

Color: Coral Style: Corded NRR: 33dB

Material: Polyurethane Foam Shape: Bell

Size: Universal

Packaging: 100 pair of Earplugs per box

Specification: The world's most-used polyurethane foam earplug, Bell shape delivers maximum in-ear comfort, Contoured design easier to insert, resists tendency to backout of ear canal, Polyurethane foam enhances comfort, especially for long-term wear, Smooth, soil-resistant closed cell-foam skin prevents dirt build-up, Bulk refills for Leight® Source 400 and Leight® Source 500 Earplug Dispensers save

time, waste and space

Honeywell Laser Lite® Earplugs



Model Number: LL-1 Color: Magenta / Yellow

Style: Uncorded NRR: 32dB **SNR**: 35dB

Material: Polyurethane Foam

Shape: T-Shape Canada Class: A(L)

Specification: Vibrant colors make protection visible, Selfadjusting polyurethane foam expands to fit virtually every wearer Contoured T-shape for easy insertion and wear Smooth, soil-resistant closed cell-foam skin prevents dirt build-up, Available in paper bag packaging and/or with cotton cords for process industries [pulp & paper] Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time, waste and space (ANSI



Honeywell Laser Lite® Earplugs



Model Number: LL-30 Color: Magenta / Yellow

Style: Corded NRR: 32dB **SNR**: 35dB

Material: Polyurethane Foam

Shape: T-Shape Canada Class: A(L)

Specification: Vibrant colors make protection visible, Selfadjusting polyurethane foam expands to fit virtually every wearer Contoured T-shape for easy insertion and wear Smooth, soil-resistant closed cell-foam skin prevents dirt build-up, Available in paper bag packaging and/or with cotton cords for process industries [pulp & paper] Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time, waste and space



Honeywell Max Lite® Earplugs



Model Number: LPF-1

Color: Green Style: Uncorded NRR: 30dB SNR: 34dB

Material: Polyurethane Foam Shape: T-Shape

Canada Class: A(L)

Specification: Ideal size for workers with smaller ear canals, Low pressure polyurethane foam expands gently for comfortable long-term wear,, Contoured T-shape for easy handling and wear, Smooth, soil-resistant closed cell-foam skin prevents dirt build-up, Optional style with attached cotton cord and paper bag packaging suitable for pulp & paper and other process industries with zero tolerance for packaging waste requirements, Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time,

waste and space



Honeywell Max Lite® Earplugs



Model Number: LPF-30

Color: Green Style: Corded NRR: 30dB **SNR:** 34dB

Material: Polyurethane Foam

Shape: T-Shape Canada Class: A(L)

Specification: Ideal size for workers with smaller ear canals, Low pressure polyurethane foam expands gently for comfortable long-term wear,, Contoured T-shape for easy handling and wear, Smooth, soil-resistant closed cell-foam skin prevents dirt build-up, Optional style with attached cotton cord and paper bag packaging suitable for pulp & paper and other process industries with zero tolerance for packaging waste requirements, Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time,

waste and space

Honeywell AirSoft® Earplugs



Model Number: AS-30R

Color: Blue Style: Uncorded NRR: 27dB SNR: 30dB

Material: TPE

Shape: 4 Flange Canada

Class: A

Specification: Advanced air pocket design features internal noise-blocking fins, Four-flange profile creates better seal in the ear canal, Less pressure in the ear canal eliminates that "plugged up" feeling, Rounded flanges, tapered shape fits better in the ear canal, Firm stem facilitates easy insertion and removal, Outstanding noise-blocking protection (ANSI



Honeywell Quiet® Earplugs



Model Number: QD-30

Color: Orange

Style: Uncorded / Polycord

NRR: 26dB SNR: 28dB

Material: Vinyl Shape: Bell Canada Class: A(L)

Specification: Patented "no-roll" design is easy to handle and

fit, Contoured shape comfortably matches contours

of the ear canal, Smooth, non-irritating skin provides all-day

comfort, easy to clean for long-term use,

Built-in insertion stem makes insertion quick and easy



Honeywell SmartFit® Earplugs



Model Number: SMF-30

Color: Orange

Style: Detachable Nylon Cord

NRR: 25dB **SNR**: 30dB Material: TPE Shape: 3 Flange Canada Class: A(L)

Specification: Patented Conforming Material Technology uses body heat to adapt to the individual shape of each wearer's ear canal, Delivers superior comfort and a truly individual fit, Simplifies inventory control - a single product fits almost every wearer, Detachable cord system and HearPack storage case (ANSI



Blue Eagle EM62 Earmuffs



Model Number: EM62

Color: Yellow NRR: 17dB

Specification: Light in weight, It can be worn in 3 positions -

Overhead, behind neck or under chin,

Complied with ANSI



Blue Eagle EM65 Earmuffs



Model Number: EM65

Color: Yellow NRR: 15dB

Specification: Light in weight, The headband can be folded, It can be worn in 3 positions - Overhead, behind neck or under

chin, Complied with ANSI



Blue Eagle EM66 Earmuffs



Model Number: EM66

Color: Orange NRR: 24dB

Specification: Impact-resistant ABS ear cup, the headband can be folded, it can be worn in 3 positions - - Overhead,

behind neck or under chin, Complied with ANSI



Blue Eagle EM92 Earmuffs



Model Number: EM92 Color: Red NRR: 24dB

Specification: Very confortable to wear, foam ear cushion, foam head cushion, suitable for continuous use over long periods, it can be worn in 3 positions - - Overhead, behind

neck or under chin, Complied with ANSI





Honeywell Clarity® Earmuffs



Model Number: C1H Color: Metallic Blue Style: Helmet Material: Plastic

NRR: 20dB

Packaging: Individual Box

Canada: B

Specification: Uniform attenuation allows wearer to hear coworkers, instructions, and other important sounds more naturally while blocking out harmful noise, Dielectric construction suitable for all workplaces, especially electrical environments, Uniform headband pressure for all head sizes, providing better comfort for long-term wear, Inner-ventilated headband minimizes pressure on the head, breathes easier in warm/humid climates, Non-deforming outer headband withstands rough treatment in the toughest workplaces, Quick-Click height adjustment remains fixed during wear, Snap-in ear cushions make replacement quick and easy



Honeywell Leightning® Earmuffs



Model Number: : L1 Color: Light Gray Style: Headband NRR: 25dB

Specification: Contemporary low profile style, Affordable, entry-level price point, Adjustable foam headband and super soft ear cushions, Black headband with light gray earcups





Honeywell Leightning® Earmuffs



Model Number: L1H **Color**: Light Gray Style: Helmet Material: Metal


NRR: 23dB

Packaging; Individual Box

Canada: B[L]

Specification: Robust steel headband withstands demanding use, especially in tough environments, Snap-in ear cushions make replacement quick and easy, Padded foam headband delivers long-wearing comfort with minimal pressure on the head, Three attenuation levels allow for targeted attenuation for a variety of applications, Telescopic height adjustment remains fixed during use, Delivers high degree of comfort; ideal for situations where compact earmuffs and reliable Noise-Blocking protection are required, Helmet earmuffs available to fit a variety of hard hats, including Honeywell North® Hard Hats

Honeywell Leightning® Hi-Visibility Earmuffs



Model Number: L1H-HV Color: Bright Green Style: Helmet

NRR: 23dB

Packaging: Individual Box

Canada: B[L]

Specification: Bright green earcups provide high visibility and contrast, Reflective padded headband illuminates under light for increased visibility and safety, Ideal to wear at night, during the day, in low light and under inclement weather conditions, Patented Air Flow Control™ technology provides optimal attenuation across all frequencies, Robust steel headband withstands demanding use, especially in tough environments, Snap-in ear cushions make replacement quick and easyPadded foam headband delivers long-wearing comfort with minimal pressure on the head, Telescopic height adjustment remains fixed during use (ANSI



Honeywell Leightning® Earmuffs



Model Number: L1N Color: Light Gray Style: Neckband NRR: 25dB

Specification: Sleek, anatomic behind-the-neck design, Ideal when wearing caps or hats, Includes headband strap for

better positioning, Light gray earcups





Honeywell Leightning® Earmuffs



Model Number: L2 Color: Dark Gray Style: Headband NRR: 27dB

Specification: Air Flow Control™ Technology provides better, consistent attenuation, especially at low frequencies, Optimal protection for virtually all noise frequency environments, Robust design withstands demanding use, especially in tough environments, Snap in ear cushions makes cushion replacement quick and easy, Padded foam headband delivers long wearing comfort, Minimal headband pressure on the head, Telescoping height adjustment for individual setting and personalized comfort, and remains fixed during use, Contemporary design improves worker acceptance and compliance, Medium profile cup



Honeywell Leightning® Earmuffs



Model Number: L3

Color: Black Style: Headband NRR: 30dB

Specification: High attenuation earmuff, Lightweight earmuff combines maximum protection and contemporary style, Adjustable headband offers a custom fit, Super soft ear cushions that deliver long-wearing comfort, Black headband

with black earcups



Honeywell Leightning® Hi-Visibility Earmuffs




Model Number: L2F-HV Color: Bright Green Style: Folding

NRR: 27dB **Material**: Metal

Specification: Bright green earcups provide high visibility and contrast, Reflective padded headband illuminates under light for increased visibility and safety, Ideal to wear at night, during the day, in low light and under inclement weather conditions, Patented Air Flow Control™ technology provides optimal attenuation across all frequencies, Robust steel headband withstands demanding use, especially in tough environments, Snap-in ear cushions make replacement quick and easyPadded foam headband delivers long-wearing comfort with minimal pressure on the head, Telescopic height adjustment remains fixed during use



Honeywell Leightning® Earmuffs



Model Number: L3H

Color: Black Style: Helmet Material: Metal NRR: 27dB

Packaging: Individual Box

Canada: A[L]

Specification: Robust steel headband withstands demanding use, especially in tough environments, Snap-in ear cushions make replacement quick and easy, Padded foam headband delivers long-wearing comfort with minimal pressure on the head, Three attenuation levels allow for targeted attenuation for a variety of applications, Telescopic height adjustment remains fixed during use, Delivers high degree of comfort; ideal for situations where compact earmuffs and reliable Noise-Blocking protection are required, Helmet earmuffs available to fit a variety of hard hats, including Honeywell North® Hard Hats.

23



Honeywell Leightning® Hi-Visibility Earmuffs



Model Number: L3-HV Color: Bright Gree Style: Headband Material: Metal NRR: 30dB

Packaging: Individual Box Canada: A[L]

Specification: Bright green earcups provide high visibility and contrast, Reflective padded headband illuminates under light for increased visibility and safety, Ideal to wear at night, during the day, in low light and under inclement weather conditions, Patented Air Flow Control™ technology provides optimal attenuation across all frequencies, Robust steel headband withstands demanding use, especially in tough environments, Snap-in ear cushions make replacement quick and easyPadded foam headband delivers long-wearing comfort with minimal pressure on the head, Telescopic height adjustment remains fixed during use (ANSI

Honeywell Thunder® Earmuffs



Model Number: T3

Color: Black Style: Headband Material: Plastic NRR: 30dB

Packaging: Individual Box

Canada: A

Specification: Dielectric construction suitable for all workplaces, especially electrical environments, Uniform headband pressure for all head sizes, providing better comfort for long-term wear, Non-deforming outer headband withstands rough treatment in the toughest workplaces, Quick-Click height adjustment remains fixed during wear, Snap-in ear cushions make replacement quick and easy, Helmet earmuffs available to fit a variety of hard hats, including Honeywell North® Hard Hats





Blue Eagle NP305 Single Respirator



Model Number: NP305

Color: Black
Material: TPR

Specification: Single filter cartridge, Twin exhalation valve, Use with RC series filters: RC201, RC202, RC203, RC205,

RC206, RC209.

Blue Eagle NP306 Double Respirator



Model Number: NP306

Color: Black Material: TPR

Specification: Twin filter cartridge, Twin exhalation valve, Use with RC series filters: RC201, RC202, RC203, RC205, RC206,

RC209

Blue Eagle RC201 Cartridge



Model Number: RC201

Specification: Use with NP305 and NP306, for dust

Blue Eagle RC202 Cartridge



Model Number: RC202

Specification: Use with NP305 and NP306, for organic

vapours. mists and fumes of low toxicity



Blue Eagle RC203 Cartridge



Model Number: RC203

Specification: Use with NP305 and NP306, for spray painting

and organic vapours of low toxicity

Blue Eagle RC205 Cartridge



Model Number: RC205

Specification: Use with NP305 and NP306, for acid gases of

low toxicity

Blue Eagle RC206 Cartridge



Model Number: RC206

Specification: Use with NP305 and NP306, for organic,

inorganic vapours and acid gases of low toxicity

Blue Eagle RC209 Cartridge



Model Number: RC209

Specification: Use with NP305 and NP306, for agricultural

sprays



Blue Eagle PF5 Dust Filter



Model Number: PF5

Specification: Use with NP305 and NP306, Can be used as prefilter for cartridge/filter, that can make your cartridge/filter to have a longer life. (Before lock up your cartridge, you put one piece of dust filter on the top of cartridge/filter.

Blue Eagle NP307 Single Respirator



Model Number: NP307

Color: Black Material: TPR

Specification: Single filter cartridge, Twin exhalation valve,

Use with RC series filters: RC1, RC2, RC3, RC5,

RC6, RC9.

Blue Eagle NP308 Single Respirator



Model Number: NP308

Color: Black Material: TPR

Specification: Twin filter cartridge, Twin exhalation valve, Use

with RC series filters: RC1, RC2, RC3, RC5,

RC6, RC9.

Blue Eagle RC1 Cartridge



Model Number: RC1

Specification: Use with NP307 and NP308, for dust



Blue Eagle RC2 Cartridge



Model Number: RC2

Specification: Use with NP307 and NP308, for organic vapors

mists and fumes of low toxicity.

Blue Eagle RC3 Cartridge



Model Number: RC3

Specification: Use with NP307 and NP308, for spray painting

and organic vapors of low toxicity

Blue Eagle RC5 Cartridge



Model Number: RC5

Specification: Use with NP307 and NP308, for acid gases of

low toxicity

Blue Eagle RC6 Cartridge



Model Number: RC6

Specification: Use with NP307 and NP308, for organic, inorganic vapours and acid gases of low toxicity



Blue Eagle RC9 Cartridge



Model Number: RC9

Specification: Use with NP307 and NP308, for agricultural

sprays

Blue Eagle PF7 Dust Filter



Model Number: PF7

Specification: Use with NP307 and NP308, Can be used as prefilter for cartridge/filter, that can make your cartridge/filter to have a longer life. (Before lock up your cartridge, you put one piece of dust filter on the top of cartridge/filter.

Blue Eagle PF3A Filter



Model Number: PF3A

Specification: Use with NP22A, activated carbon dust filter

Blue Eagle NP303 Single Respirator



Model Number: NP303

Color: Black Material: TPR

Specification: Single filter cartridge, Twin exhalation valve,

Use with RC101



Blue Eagle NP304 Double Respirator



Model Number: NP304

Color: Black Material: TPR

Specification: Twin filter cartridge, Twin exhalation valve, Use

with RC101

Blue Eagle RC101 Cartridge



Model Number: RC101

Specification: Use with NP303 and NP304, Dust filter

Blue Eagle NP22 Dust Mask



Model Number: NP22

Specification: Comfortable wearing, The mask is to block

unusual smell, fine dust, and small particles

Blue Eagle PF2 Filter



Model Number: PF2

Specification: Use with NP22, Dust Filter



Honeywell FFP3 NR D with Valve



Model Number: FFP3

Specification: Folding respirator packed in a tightly sealed

individual bag to prevent contamination.

Fluid-resistant outer shell to reduce risks of contamination. Ultra-soft hypoallergenic Willtech™ nose seal with absorption properties and a tight film. Preformed and coloured nose bridge to save time to perfectly adjust the mask and to instantly identify its protection level. Shielded exhalation valve with an exclusive design to breathe easily and to avoid any risk of leakage due to a membrane damage. Vast interior volume with built-in chin piece for a better fit and a communication made easier. Elasticated sliding straps, highly flexible and resistant, to increase comfort and safety and to ease donning/doffing. Lightweight respirators (15g) to reduce wearers'fatigue. No latex, no silicone, nor PVC. Dolomitetested. Box dispenser to save time.

Honeywell H801V N95 w/ Valve



Model Number: H801V Protection level: KN95

Material: non-woven fabric and electrostatic fiber

Specification: Anti PM2.5, anti fog, dustproof, anti bacteria



NOSH

Honeywell H801 N95 Particulate Respirator



Model Number: H801 Size: 25 x 14 x 17

Weight: 0.4kg

Specification: Value priced high quality N95 mask, Enhanced

comfort due to easily adjustable nose bridge,

Extra smooth foam strip inside the mask, Easy to breathe

through because of robust filter media





Honeywell RU8500 Series Half Mask



Model Number: RU8500

Specification: Silicone face piece is soft and flexible to provide workers with a comfortable fit for hours of use, Dual flange silicone provides a more comfortable and secure fit, Features a speaking diaphragm offer better speech clarity for improved communication.



Honeywell RU6500 Series Full Facepiece



Model Number: RU6500

Specification: Choose from a 5-point strap or industrial mesh headnet to fit your comfort and needs, Silicone skirt offers exceptional durability and comfort,

All straps are atached to the rim of the facepiece, rather than the silicone skirt, to reduce pressure points and distortion of the sealing surface when thightened, Replaceable, high impact resistant polycarbonate lens treated with anti-scratch coating Mask designed with a wide viewing area offering distortion free visibility and optical clarity





Model Number: 550030M

Size: Medium

Specification: The North 550030M is a low cost and disposable version of the 7700 series of half masks. They are comfortable and efficient in design just like the 7700 series. All the parts of this mask are replaceable, extending the lifetime of the respirator. This mask is size medium. Available in sizes small, medium and large







Honeywell N75001L Cartridge

Model Number: N75001L

Specification: Organic Vapor, Approved for use against organic

vapors





Honeywell N75002L Cartridge

Model Number: N75002L

Specification: Acid Gas Cartridge, Approved for use against acid gases (Chlorine, Hydrogen Chloride, Sulfur Dioxide, Hydrogen Fluoride and Chlorine Dioxide) and Formaldehyde



Honeywell N750031L Cartridge



Model Number: N750032L

Specification: Organic Vapor, Chlorine, Hydrogen Chloride, Sulfur

Dioxide, Hydrogen Fluoride, Chlorine Dioxide Cartridge



Honeywell N75004L Cartridge



Model Number: N75004L

Specification: Ammonia & Methylamine, Approved for use against

Ammonia & Methylamine



Honeywell N750052L Cartridge



Model Number: N750052L

Specification: Mercury Vapor Cartridge with ESLI

Mercury Vapor and Chlorine with End-of-Service Life Indicator

(ESLI) for Mercury Vapor

T*iosh*

Color Coded Label Hazard Identification

Organic Vapors (OV)

Acid Gases (AG)

Organic Vapors and Acid Gases (OV/AG) Ammonia or Methylamine (AM/MA)

Multi-Contaminant (MC)

Mercury Vapor or Chlorine (MV/CL)

P100- All Particulates



Cotton Gloves (Light Duty)



Specification: Knit construction for general use.

Cotton Gloves (Medium Duty)



Specification: Knit construction for general use.

Cotton Gloves (Heavy Duty)



Specification: Knit construction for general use.

Cotton Gloves (Colored)



Specification: Knit construction for general use.

Cotton Dotted Gloves



Specification: PVC dotted on one side for good grip



A2025 Leather Gloves



Model: A2025

Size: 14 Inches, 16 Inches

Specification: Split type long leather gloves for general

purpose

Leather Tig Gloves



Specification: Splittypelongleatherglovesforgeneral purpose

SR-22 Leather Gloves



Model: SR-22 Size: Large

Specification: Split type long leather gloves for welding

SR-44 Leather Gloves



Model: SR-22 Size: Large

Specification: Split type long leather gloves for welding

PR-22 Leather Gloves



Model: PR-22 Size: Large

Specification: Split type long leather gloves for welding



PR-44 Leather Gloves



Model: A2025

Size: 14 Inches, 16 Inches

Specification: Split type long leather gloves for general

purpose

LP-44 Leather Gloves



Specification: Splittypelongleatherglovesforgeneral purpose

PVC Gloves



Model: SR-22 Size: Large

Specification: Split type long leather gloves for welding

North Tower Chemical Gloves



Model: SR-22 Size: Large

Specification: Split type long leather gloves for welding

Greenfield Rubber Coated B Gloves



Model: PR-22 Size: Large

Specification: Split type long leather gloves for welding



PR-44 Leather Gloves



Model: A2025

Size: 14 Inches, 16 Inches

Specification: Split type long leather gloves for general

purpose

LP-44 Leather Gloves



Specification: Splittypelongleatherglovesforgeneral purpose

PVC Gloves



Model: SR-22 Size: Large

Specification: Split type long leather gloves for welding

North Tower Chemical Gloves



Model: SR-22 Size: Large

Specification: Split type long leather gloves for welding

Greenfield Rubber Coated B Gloves



Model: PR-22 Size: Large

Specification: Split type long leather gloves for welding



Hand Protection

Honeywell Electrical Gloves



Specification: Latex gloves offer the wides range of conditions for use form 650 Volts to 4000 Volts and posses high dielectric characteristics, making them perfect for use in many electrical applications, from low voltage to high voltage. Available in 2.5 KV, 5 KV, 10 KV, 20 KV, 30 KV and 40 KV

 ϵ

Honeywell Overprotective Gloves



Specification: Yellow cowhide grain leather overglove Water-repellent and silicon treatment Gunn cut, thumb in one piece, gauntless Velcro® adjustment strap on the back 150 mm split leather cuff sewed outside

Honeywell Cryogenic Gloves



Specification: Water-repellent silicone cowhide grain leather glove, Fully lined with 2 aluminium/fleece layers Gunn cut, winged thumb, crispin type Reinforcement between thumb and index 200 mm split leather cuff





Nitriguard Plus™ - LA132G



Size: S, M, L, XL

Specification: Provide and effective replacement for neoprene, natural rubber and vinyl supported gloves. The LA132G resist punctures and abrasions, while flock lining gives extra comfort working with oils, petroleum solvents, or greases. CE

Phillyx Nitrille Gloves



Size: L, XL

Specification: Double wall thickness: ± 0.93 mm

- Pure cotton flock line nitrile formula glove
- •Open cuff allows natural ventilation to keep hand cool Does not contain latex protein, suitable for sensitive skin
- Compliant for food contact
- •Good abrasion and puncture resistance for long lasting
- •High resistance to many solvents and oil based chemicals
- Highly flexible and comfortable for an excellent dexterity
- •Superior raised diamond grip pattern on palm to ensuring good grip in both wet & dry conditions

Certificate: EN 420, EN 388:2003, EN 374-1:2003

 ϵ



Aluminized Wear

Blue Eagle AL1 Aluminized Hood



Model: AL1

Material: Woven fabric of a modified acrylic fiber over a fiberglass core yarn, aluminized one side

Specification: The aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, The aluminized clothings are tested according the following methods

Blue Eagle AL2 Aluminized Coat



Model: AL2

Material: Woven fabric of a modified acrylic fiber over a fiberglass core yarn, aluminized one side

Specification: The aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, The aluminized clothings are tested according the following methods

Blue Eagle AL3 Aluminized Trouser



Model: AL3

Material: Woven fabric of a modified acrylic fiber over a fiberglass core yarn, aluminized one side

Specification: The aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, The aluminized clothings are tested according the following methods

Blue Eagle AL4 Aluminized Boots



Model: AL4

Material: Woven fabric of a modified acrylic fiber over a fiberglass core yarn, aluminized one side

Specification: The aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, The aluminized clothings are tested according the following methods



Aluminized Wear

Blue Eagle AL5 Aluminized Gaiters



Model: AL5

Material: Woven fabric of a modified acrylic fiber over a fiberglass

core yarn, aluminized one side

Specification: The aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, The aluminized clothings are tested according the following methods

Blue Eagle AL6 Aluminized Apron w/ Sleeves



Model: AL6

Material: Woven fabric of a modified acrylic fiber over a fiberglass

core yarn, aluminized one side

Specification: The aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, The aluminized clothing's are tested according the following methods

Blue Eagle AL7 Aluminized Apron



Model: AL3

Material: Woven fabric of a modified acrylic fiber over a fiberglass core yarn, aluminized one side

Specification: The aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, The aluminized clothing's are tested according the following methods

Blue Eagle AL8 Aluminized Sleeves



Model: AL8

Material: Woven fabric of a modified acrylic fiber over a fiberglass

core yarn, aluminized one side

Specification: The Aluminized clothing is designed to provide protections against thermal and mechanical risks, Ideal for use in steel mills, casting shops, heat treating operations and foundries, the aluminized clothings are tested according the following methods



Aluminized Wear

Blue Eagle AL145 Aluminized Protective Gloves



Model: AL145

Material: Woven fabric of a modified acrylic fiber over a

fiberglass core yarn, aluminized one side

Specification: Providing protections against thermal and

mechanical risks, Max.: 250 degrees C

Length: 14" (five fingers)

Blue Eagle AL165 Aluminized Protective Gloves



Model: AL165

Material: Woven fabric of a modified acrylic fiber over a

fiberglass core yarn, aluminized one side

Specification: Providing protections against thermal and

mechanical risks, Max.: 250 degrees C

Length: 16" (five fingers



Safety Vest (Mesh Type)



Specification: High-visibility (HV) clothing, a type of personal protective equipment (PPE), is any clothing worn that has highly reflective properties or a colour hat is easily discernible from any background

Safety Vest (Cloth Type)



Specification: With 2" width silver high visiblity reflective tape horizontal bands around the torso, provides maximum visibility for safety. lightweight and durable, refrains it's color under toughest weather

Traffic Gloves



Specification: visibility that surpasses that of standard gloves, reflective gloves are ideal for traffic control, and they help protect emergency professionals.

Traffic Baton



Specification: Baton light used for traffic for visiblity to control traffic

Traffic Cone



Specification: Traffic cone are usually cone-shaped markers that are placed on roads or footpaths to temporarily redirect traffic in a safe manner.



Caution Barricade Tape



Size: 3" x 1000"

Specification: High visibility, non adhesive, lightweight, economical reusable, for marking physical hazards, traffic,

etc. to prevent the accidents

Danger Barricade Tape




Size: 3" x 1000"

Specification: High visibility, non adhesive, lightweight, economical reusable, for marking physical hazards, traffic,

etc. to prevent the accidents

Hella LED Buggy Whip



Specification: visibility that surpasses that of standard gloves, reflective gloves are ideal for traffic control, and they help protect emergency professionals.



KING'S KR7000X Low Cut Safety Shoes



Description

Black tango print leather laced shoe.

Sizes: 5-12 US, no half sizes

SOLE CONSTRUCTION

Single density polyurethane sole Oils and acids/alkalis resistant Impact resistant carbon steel toe cap Slip-resistant polyurethane (PU) outsole Antistatic.

UPPER CONSTRUCTION

Non-woven fiber insole board Full-length EVA insole made thicker for extra comfort Taibrelle lining.

KING'S KWS701X Mid Cut Safety Shoes



Description

Black full grain printed leather laced shoe.

Sizes: 5-12 US, no half sizes

SOLE CONSTRUCTION

Single density lightweight and slip resistant polyurethane (PU) sole (SRC outsole) Oils and acids/alkalis resistant Anti-static

UPPER CONSTRUCTION

Breathable non-woven fabric lining Anti-static insole board Extra wide 5-toecap provides maximum comfort for your toes 200 Joules steel toecap for impact and compression resistance. Extra thick full length fabric-lined EVA foam insole with shock absorption, anti-bacterial and anti-static properties.



KING'S KWD901KX High Cut Safety Shoes



Description

Brown full grain printed leather laced shoe.

Sizes: 5-12 US, no half sizes

SOLE CONSTRUCTION

Dual density lightweight and slip resistant polyurethane (PU)

sole (SRC outsole)

Oils and acids/alkalis resistant Anti-static

UPPER CONSTRUCTION

Breathable non-woven fabric lining. Anti-static insole board Extra wide 5-toe toecap provides Maximum comfort for your toes. 200 Joules steel toecap for impact and compression resistance PUshion Insole: Extra thick full length fabric-lined PU foam insole with shock absorption, anti-bacterial and antistatic properties

KING'S KWD805CX Pull up Boots



Brown full grain printed leather Pull-up boots

Sizex: 5-12 US, no half sizes

SOLE CONSTRUCTION

Lightweight & slip resistant dual density polyurethane (PU) sole with softer midsole to cushion shock impact (SRC Outsole)

Oils and acids/alkalis resistant

Anti static




Breathable non-woven fabric lining

Antistatic insole board

Scuff cap for toe bumper protection

Extra wide 5-toe toecap provides maximum comfort for your

200 Joules steel toe cap for impact and compression resistance PUshion Insole: Extra thick full length, fabric-lined PU foam insole with shock absorption, anti-bacterial and anti-





Adela AUL50X3 Web Sling (2in x 3m)



Strap Width: 50mm Loop Length: 350mm Sewing Length: 350mm Loop Width: 25mm

Length: 3 meters Working Load: 2 tons

Specification: Designed to bear heavy loads and lift them

softly

Adela AUL50X6 Web Sling (2in x 6m)



Strap Width: 50mm Loop Length: 350mm Sewing Length: 350mm Loop Width: 25mm

Length: 6 meters Working Load: 2 tons

Specification: Designed to bear heavy loads and lift them

softly

Adela AUL75X3 Web Sling (3in x 3m)



Strap Width: 75mm Loop Length: 400mm Loop Width: 35~40mm Sewing Length: 400mm

Length: 3 meters Working Load: 3 tons

Specification: Designed to bear heavy loads and lift them

softly

Adela AUL75X6 Web Sling (3in x 6m)



Strap Width: 75mm Loop Length: 400mm **Loop Width:** 35~40mm Sewing Length: 400mm

Length: 3 meters Working Load: 3 tons

Specification: Designed to bear heavy loads and lift them

softly



Adela H-4501 Body Harness



Model number: H-4501

Standard: EN361: 2002 compliance

Specification: 45mm width polyester webbing, 1 x Dorsal Dring, Front chest adjustable belt, Detatchable waist belt, Both

thighs quick fit buckles

Adela H-4538 Body Harness w/ Big Hook



Model number: H-4538

Standard: EN361: 354 compliance

Specification: 45mm width polyester webbing, 1 x Dorsal Dring, Front chest adjustable belt, Detachable waist belt, Both thighs quick fit buckles, CE 0229 EN354/355, Diameter 14mm

x 1.5M, Screw-lock carabiner x 1, Hook H-3101 x 1

Adela HKW-4503 Body Harness



Model number: HKW-4503

Standard: CE 0321 EN361:358 2002 certificated

Specification: 5 anchors attaching points, 45mm width polyester webbing, Shoulder straps adjustable, Ergonomics back support pad, Waist support pad within 2 lateral D-rings, Additional attachments behind two hips, Both legs with

support pad / adjustable buckles

Adela HKW-4502 Body Harness



Model number: HKW-4502

Standard: EN361:358 2002 compliance

Specification: 5 anchors attaching points, 45mm width polyester webbing, Shoulder straps adjustable, Ergonomics back support pad, Waist support pad within 2 lateral D-rings / fasten by quick release buckle, Additional attachments behind two hips, Both legs with support pad with quick release buckles, Front chest adjustable belt, Front Chest 2 attaching

points



Adela H-5001 Body Harness



Model number: H-5001

Standard: EN361: 2002 compliance

Specification: 50mm width polyester webbing, 1 x Dorsal Dring, Front chest adjustable belt, Detatchable waist belt, Both

thighs quick fit buckles

Adela CH-4501 Seat Harness



Model number: CH-4501

Specification: Adjustable leg loops allow suitable length, Detachable elastic thigh loop straps, Comfortable and pliable webbing minimize the pressure suitable for maximum waist

size to 110cm(43")

Adela CH-4502 Seat Harness



Model number: CH-4502

Specification: Adjustable leg loops allow suitable, Waist pad with lateral gear loops, Detachable elastic thigh loop strap, Comfortable and pliable webbing to minimize the pressure suitable for maximum waist size from 85~110cm

Adela H-209 Lanyard(Rope) w/ Small Hook



Model number: H-209 Standard: CE 0299 EN354

Specification: Diameter 14mm x 1.5M, Screw-lock carabiner

x1, Hook H-2101 x1

Adela H-309 Lanyard(Rope) w/ Big Hook



Model number: H-309 **Standard:** CE 0299, EN354

Specification: 1.5m Lanyard with 1x 53mm Opening Large Snap Hook & 1x Carabiner, Diameter 14mm x 1.5M, Loop at

ends

CE



Adela EF-31 Lanyard(Rope) w/ Shock Absorber



Model Number: EF-31

Standard: CE 0299 EN354/355

Specification: Diameter 14mm x 1.5M, Screw-lock carabiner x1, Hook H-3101 x1, Single Lanyard w/ Shock Absorber and

Big Hook

 ϵ

Adela EF-32 Lanyard(Rope) w/ Shock Absorber



Model Number: EF-32


Standard: CE 0299 EN354/355

Specification: Diameter 14m x 1.5M, Screw-lock carabiner x1, Hook H-3101 x2, Double Lanyard w/ Shock Absorber and Big

Hook

 ϵ

Adela WF-31 Lanyard(Webbing) w/ Shock Absorber



Model Number: WF-31

Specification: 45mm wide x 1.5M, Screw-lock carabiner x1, Hook H-3101 x1, Single Lanyard w/ Shock Absorber and Big

Hook

Adela WF-32 Lanyard(Webbing) w/ Shock Absorber



Model Number: WF-32

Specification: 45mm wide x 1.5M, Screw-lock carabiner x1, Hook H-3101 x2, Double Lanyard w/ Shock Absorber and Big

Hook



Adela WFL-31 Lanyard(Webbing) w/ Shock



Model Number: WFL-31 **Standard:** CE 0299, EN354/355

Specification: 45mm wide x 1.5M, Screw-lock carabiner x1, Hook H-3101 x1, Single Lanyard w/ Shock Absorber and Big

Hook

 ϵ

Adela WFL-32 Lanyard(Webbing) w/ Shock Absorber



Model Number: WFL-32 **Standard:** CE 0299, EN354/355

Specification: 45mm wide x 1.5M, Screw-lock carabiner x1, Hook H-3101 x2, Double Lanyard w/ Shock Absorber and Big

Hook

 ϵ

Adela H-8621 Rope Grab w/ Lanyard (Small Hook



Model Number: H-8621

Hook: H-2101 (18mm opening)

Chock: H-8706 (opening for 16mm diameter rope) Various

choke hooks are available

Rope length: 35mm Rope width: 13mm

Adela H-8631 Rope Grab w/ Lanyard (Big Hook)



Model Number: H-8631

Hook: H-3101

Chock: H-8706 (opening for 16mm diameter rope) Various

choke hooks are available

Rope length: 35mm Rope width: 13mm



Adela H-8706 Rope Grab Open Type



Model Number: H-8706

Specification: Rope grab for 14-16mm rope. Guided fall

arester on rope, Weight capacity: 100kg

Adela H-117 Lineman Safety Belt



Model Number: H-117

Specification: Lineman safety Belt with Pole Strap

Adela H-132 Lineman Safety Belt (Big Hook)



Model Number: H-132

Specification: Lineman safety Belt with Pole Strap

Adela H-227 Lineman Safety Belt



Model Number: H-227

Specification: Electric tower climbing waist position belt,.

1.2M max length adjustable, Fall arrest rope grab

Adela RFA-060 Retractable Fall Arrestor



Model Number: RFA-060

Cable: Material 1-8/18" (35mm) Polyester webbing

Capacity: 4850lbs(21kN)

Length: 6Mattached with steel swivel Hook H-7102(CE0299

EN362:2004)

Specification: P.P. Housing and Drum, Lightweight & durable & resistant to corrosion, built-in galvanized steel swivel eye



Adela RFA-060W Retractable Fall Arrestor



Model Number: RFA-060W

Material: 1-8/18"(35mm) Polyester webbing

Capacity: 4850lbs(21kN)

Length: 6M attached with steel swivel Hook H-7102(CE0299

EN362:2004)

Weight: 9.3lbs(4.2kgs)

Specification: Lightweight, durable and resistant to corrosion

Adela RT-025 Rescue Tripod (15M



Model Number: RT-025

Cable Length: 15M Max Height: 2.2M

Specification: Designed for durability and light weight, the tripod is easy to set up and transport by aluminum section tripod, Cast Aluminum Head has an integral Stainless Steel Pulley to accommodate a winch with quickmount bracket

Adela Safety Rope (10MM x 200M)



Specification: Used to support emergency services personal and civilians during training, rescue and fire fighting

Adela Safety Rope (11MM x 200M)



Specification: Used to support emergency services personal and civilians during training, rescue and fire fighting



Adela AF-09 Screw Lock Carabiner



Lock Device: Screw Lock Model Number: AF-09 **Certification:** CE EN362 Gate Open: 16mm Material: Steel Length: 107mm Strength: 22kN Weight: 160g

Adela AF-10 Steel Carabiner Screwgate



Model Number: AF-10 Lock Device: Screw Lock **Certification:** CE EN362 Gate Open: 22mm Length: 113mm Material: Steel Strength: 35kN Weight: 222g

Adela AF-10K



Certification: CE EN362 Material: Steel Strength: 35kN Lock Device: Screw Lock Gate Open: 26mm Length: 124mm

Weight: 213g

Adela AF-11 Steel Carabiner Screwgate



Model Number: AF-11 **Lock Device:** Screw Lock **Certification:** CE EN362 Gate Open: 25mm Material: Carbon Steel Length: 122mm Strength: 35kN Weight: 237g

Adela AF7206 Climbing Ascension Ascender



Certification: CE EN362:1997 Model Number: AF7206

Strength: 4Kn Material: Aluminum

Weight: 239g Specification: Left Hand

Adela AF-7207 Chest Croll Ascender



Model Number: AF-7207 Material: Aluminum Alloy

Weight: 162g Rope: Ø8~Ø13mm



Adela AF-78 Figure 8 Descender



Model Number: AF-78 Material: Aluminum Alloy

Certification: CE EN362 Strength: 30kN

Length: 14.5mm

Inner Diameter: Big: 52mm Small: 26mm

Specification: Rope Descender Ascender, Hot Forged

Adela AF-79 Figure 8 Descender w/ Oxhorn



Model Number: AF-79 Material: Aluminum Alloy

Certification: CE EN362 Strength: 40k

Length: 14.5mm

Inner Diameter: Big: 71mm Small: 40mm

Weight: 268g

Adela AF-80B Aluminum D - Carabiner Autolock



Model Number: AF-808 Lock Device: Screw Lock **Certification:** CE EN362 Gate Open: 22mm Length: 112mm Material: Aluminum Alloy

Strength: 35kN Weight: 80g

Adela AF-84



Certification: EN362 & EN12275 Material: Aluminum Alloy

Lock Device: Screw Lock (Key Type) Strength: 22kN 7kN 6kN

Gate Open: 18mm Length: 119mm Weight: 73g

Adela AK-010 Rope Stop Backup Device



Certification: CE EN362 Material: Aluminum Alloy Strength: 15kN

Weight: 232g

Rope size: 12~14mm



Adela AG-011



Model Number: Adela AG-011 Material: Aluminum Alloy Rope Size: 8~12mm B/S: 20kN

Certificate: CE EN362 Bearings: Brass Weight: 86g

Adela AG-012 Single Sheave Pulley



Model Number: Adela AG-012 Material: Aluminum Alloy

Rope Size: Max. 16mm B/S: 24kN

Weight: 255g

Certificate: CE EN362 Bearings: Brass

Adela AG-013



Model Number: Adela AG-013 Material: Aluminum Alloy Rope Size: Max. 16mm B/S: 32kN

Weight: 440g

Certificate: CE EN362 Bearings: Brass

Adela AG-014 Tandem Pulley



Model Number: Adela AG-014 Certificate: CE EN362 Material: Aluminum Alloy Weight: 246g

Rope Size: Aluminum Axle: Max. 14mm Stainless Steel Axle:

8~10mm

Adela AG-15B



Model Number: Adela AG-15B Strength: 30kN Material: Aluminum Alloy Rope Size: 18mm

Weight: 160g

Adela ADF-698



Model Number: Adela ADF-698 Material: Aluminum Alloy

Weight: 465g

Strength: 22kN Rope Size: 10~13mm



Adela AR-01



Model Number: Adela AR-01 Material: Aluminum Alloy

Rope Size: 18mm Strength: 40kN Weight: 215g

Adela AR-02



Model Number: Adela AR-02 Material: Aluminum Alloy

Rope Size: 18mm Strength: 40kN Weight: 499g

Adela AR-03



Model Number: Adela AR-03 Material: Aluminum Alloy

Rope Size: 18mm Strength: 30kN Weight: 65g



Body Protection

Leather Sleeves



Specification: Sleeves can be used independently or in conjunction with an apron or other garment to offer optimum protection of the lower arm and elbow

Cotton Sleeves



Specification: Sleeves can be used independently or in conjunction with an apron or other garment to offer optimum protection of the lower arm and elbow.

Reusable Cover-All Suit



Material: Cotton

Specification: Hooded, zipper front, comes with pockets, lightweight, color navy blue for general purpose.

Disposable Cover-All Suit



Specification: Polypropylene spunbounded material, hooded, zipper front, elasticized wrist, waist and ankles, lightweight, color white for general purpose.

Raincoat Jacket



Material: PVC

Specification: Water-resistant coat worn to protect the body

from rain



Body Protection

Raincoat Pants



Material: PVC

Specification: Water-resistant pants worn to protect the body

from rain

Raincoat Poncho



Material: PVC

Specification: Water-resistant coat worn to protect the body from

rain

Raincoat Knee Length



Material: PVC

Specification: Water-resistant coat worn to protect the body

from rain

Back Support



Specification: Adjustable belt tension and suspenders for comfortable fit, stretchable elastic straps, use to reduce repetitive back strain

Fire Blanket



Casing: Pouch or Case

Specification: Safety device designed to extinguish incipient (starting) fires. Consists of a sheet of fire retardant material

which is placed over a fire in order to smother it



Body Protection



Maong Apron

Specification: Functional accessory to protect ones clothes and skin from incidental stains and marks



Leather Apron

Specification: Functional accessory to protect ones clothes and skin from incidental stains and marks



Maong Jacket

Specification: For safety purpose during industrial work



Leather Jacket

Specification: For safety purpose during industrial work



Maong Sleeves

Specification: Sleeves can be used independently or in conjunction with an apron or other garment to offer optimum protection of the lower arm and elbow.



Salisbury



Salisbury Pro-Wear, Arc Flash
Kit, Premium Lightweight
Coverall, Large, Fits Chest Size
42 to 44 in Fits Waist Size 36 to
38 in, 30 in Inseam, 88% Cotton,
12% Nylon, Nomex Thread,
Navy Blue, Orange, 12 cal/cm2
ATPV Rating, 2 Hazard Risk
Category, Includes Arc Flash
Hood with Face Shield, 12
cal/cm2 AS1000HAT, Safety
Glasses, ASBag, ASTM F1506, CE
0120 Certified, NFPA 70E
Standards, Flame-Resistant
Special Features

Durable

Highly Comfortable fabric allows for a generous fit to wear over your work clothing 99.9% UV protection

Keeps drier and cooler even in demanding conditions

ArcFlash Protection Salisbury SK40M

Arc Flash Kit ATPV Rating 40 cal/cm2 Gray Color Fits Chest Size 38 to 40 in 32 to 34 in Fits Waist Size Hazard Risk Category 4 29" Inseam Material 88% Cotton, 12% Nylon, Nomex Thread Size Medium Special Features Flame-Resistant Type Personal Protection UNSPSC 46181508 Applications For All Electrical Workers Standards ASTM F1506, CE 0120 Certified, NFPA 70E MFR Part # SK40M

ArcFlashProtectionSalisburySK40L

Item	Arc Flash Kit
ATPV Rating	40 cal/cm2
Color Gray	
Fits Chest Size	42 to 44 in
Fits Waist Size	36 to 38 in
Hazard Risk Category	4
Inseam	30"
Material	88% Cotton,
	12% Nylon,
	Nomex Thread
Size	Large
Special Features	Flame-Resistant
Туре	Personal Protection
UNSPSC	46181508
Applications	For All Electrical
	Workers
Standards	ASTM F1506,
	CE 0120 Certified,
	NFPA 70E
MFR Part #	SK40L-C



Salisbury





Item	Arc Flash Kit
ATPV Rating	8 cal/cm2
Color	Blue/Orange
Fits Chest Size	38 to 40 in
Fits Waist Size	32 to 34 in
Hazard Risk Category	2

Inseam 29"

Material 88% Cotton, 12% Nylon, Nomex Thread

Size Medium

Special Features Flame-Resistant Type Premium

Lightweight Coverall

UNSPSC 46181508 Standards ASTM F1506,

CE 0120 Certified,

MFR Part # SKCA8M



Arc Flash Salisbury SKCA11L

MFR Part #

ltem	Arc Rated Clothing
ATPV Rating	12 cal/cm2
Color	Blue/Orange
Fits Chest Size	42 to 44 in
Fits Waist Size	36 to 38 in
Hazard Risk Category	2
Inseam	30"
Material	88% Cotton,
	12% Nylon,
	Nomex Thread
Size	Large
Special Features	Flame-Resistant
Туре	Premium
	Lightweight
	Coverall
UNSPSC	46181508
Standards	ASTM F1506,
	CE 0120 Certified,



Wisdom

WISDOM

Model
Rated Capacity
Rated Voltage
Continious discharging time
Main light LED working voltage
Main light working curent
Main light power
Main light luminous flux
Lamp lighting degree (initial lighting in 1 m)
Main light life span
Auxiliary light power
Auxiliary life span
Short circuit protect time

Life span of the battery (Recharges) Charging time Dimensions

Main cable Weight KL5MS Standard 7800 mAh

3.7 V 13 h 3.0 V 640 mA 1.92 W 340 lm 18000 lx 100000 h 0.4 W 40000 h < 320 µs



Wisdom KL5MS CapLamp

1200 cycles (In reasonable working condition) 4-7.5H 94 x 36 x 90 mm; 3.7 x 1.4 x 3.5 in (Size of the battery box) 1.4 / 1.65 m; 4.59 / 5.41 ft 500 g; 19.40oz



Wisdom NWR-20 Portable Charger

Features AC input

DC input DC output voltage DC output current Size

Weight Charging time for KL5M Charging time for KL8M NWB-20 Specifications AC 100~240 V ± 10%, 0.24 A, 50~60 Hz 7~30 V, 1.7 A 4.20 V ± 0.05 V (max) 2000 mA ± 100 mA (max) 116 x 76 x 56 mm; 4.6 x 3.0 x 2.2 in 215 g; 7.58 oz 4.5-6.5 h 6.5 h



Wisdom



Wisdom 3A Cap Lamp

Lamp format Power supply

Light modes

Main LED duration Main LED output (brightness)

Charging time (recommended charger) Charging cycles

Total weight IP rating Warranty Cordless (integral battery)
Lithium Ion (Lilon)
battery 3.7 V / 6.2 Ah
2 - Main and Auxiliary
(Emergency)
13 hours
12,000 lux at 1m
(211 lumens)
5 hours
1,200 cycles
(in good working conditions)
175g
IP68

2 years (warranty terms of Wisdom)

Brightness Mode
Continuous discharging time (h)
LED working current (A)
Light power (W)
Initial lighting degree in 1 m (lx)
Light luminous flux (lm)
Rated capacity
Rated voltage
Main light working voltage
Main light life span
Auxiliary light power
Auxiliary light life span
Short circuit protection time
Life span of the battery (Recharges)

Charging time Dimensions Weight HI ME LO 5 13 60 1.4 0.53 0.065 4.2 1.59 0.18 25000120001400 463 211 6.2 Ah 3.7 V 3.0 V 100000 h 0.4 W 40000 h < 320 µs

1200 cycles (In reasonable working condition) 5 h

84 x 69 x 50 mm; 3.3 x 2.7 x 2.0 in

Charging time for Lamp

169 g; 5.96 oz



Wisdom NWB-30 Charger

3-5 h

64



ZOLL AED PLUS DEFIBRILLATOR (LIVE UNIT)



ZOLL AED PLUS DEFIBRILLATOR (LIVE UNIT) AED PLUS

DEFIBRILLATOR with graphical cover

includes LCD screen showing voice prompt messages, device advisory messages, elapsed time, shock count and chest compression graph. Supplied with Public

Safety PASS Cover, soft case, operators guide and five (5) year warranty + (2) year warranty if registered online.

(Replacement not Repair)

Inclusions:

- One (1) CPR-D Adult padz one piece electrode pad with Real CPR Help
- Ten (10) Type 123 Lithium Batteries
- Bag

AED Pro Automated External Defibrillator



AED Pro Automated External Defibrillator

A Flexible AED for Every Rescuer

The AED Pro® provides the support used by rescuers to nearly triple survival.1 It provides the feedback both professionals and lay rescuers need to perform optimal CPR.

It features:

- Real CPR Help® to aid rescuers in delivering optimal compressions and improving the likelihood of survival
- See-Thru CPR® to reduce the length of interruptions by removing compression artifact
- A three-lead cable for basic monitoring using ECG electrodes
- Unique extended USB storage that allows immediate data transfer without leaving the scene

AED Pro Semi-Auto/Manual Includes:

- -1ea Soft Carry Case
- -1ea Rugged Over-Molded Outer Housing
- -1 ea Operator's Guide
- -5 Years Factory Warranty
- -1pair CPR Stat-padz HVP Multi-Function CPR Electrodes. Up to twenty four month shelf-life.







ZOLL's Full-Rescue AEDs feature CPR-D-padz®, a one-piece, pre- connected electrode with Real CPR Help® feedback.

Ordinary AEDs require that the rescuer use two separate electrodes. By using CPR hand placement as the landmark, it is easy to place the CPR- D-padz on the victim quickly. The CPR-D-padz also lasts five years-the longest shelf life of any defibrillator electrode sold today

Real CPR Help

Inadequate compression rate and depth are common during CPR. Adult victims need at least 100 compressions per minute and at a depth of at least 2 inches (5 cm). Compressions must be done well to effectively move blood and oxygen.

The ZOLL AED Plus® converts compression data instantaneously from the CPR-D-padz and provides an adaptive metronome to help the rescuer with the proper rate and depth, saying "Push harder" or "Good compressions," as needed. It also shows CPR compression depth on the display screen. ZOLL's AED Plus is the only AED that helps the rescuer achieve the correct rate and depth of chest compressions during CPR. No other AED has both these capabilities.

Everything You Need for the Rescue
The CPR-D-padz comes complete with a CPR barrier mask,
scissors, disposable gloves, a prep razor, a towel, and a moist
towelette.

Duracell 123A Lithium Battery



The Zoll AED Plus takes Duracell Type 123 Lithium Batteries which are packaged in a set of ten (10) batteries.

The Duracell batteries have a five (5) year expiration date while the device is in stand-by mode and a shelf life of ten (10) years.

The AED Plus uses redundant circuitry, so if one set of five (5) batteries fails, the other five (5) are there for backup.



Pedi-padz II



Pedi-padz II

The Only Full-Rescue AED with Intelligent Pediatric Capability

The ZOLL AED Plus® Intelligent Pediatric Capability includes voice and text prompts that tell rescuers that Pedi-padz® II are connected, ensuring that the proper defibrillator electrodes are being used. When a cardiac arrest occurs, the fact is that only half of the victims will need a shock. The other half requires cardiopulmonary resuscitation (CPR).

Separate and specific algorithms for adults and children are used to analyze a victim's heart rhythm. The ZOLL AED Plus can defibrillate children up to eight years of age, using the Pedi-padz II electrodes. Separate energy levels also have been incorporated for pediatric patients. Electronics in the AED Plus adjust defibrillating energy levels automatically so that suitable doses are delivered accurately, when needed. With ECG analysis designed specifically for a pediatric heart rate, coupled with appropriate defibrillation energy levels, the AED Plus can handle both adult and pediatric rescues.

Pedi-padz II electrodes are designed especially for use with the AED Plus, and are also compatible with professional defibrillators, allowing continuity of care. The AED Plus does not rely on a resistor or other hardware in the wires to reduce delivered energy. Anatomical diagrams on the package facilitate proper pad placement.



The ZOLL® R-Series BLS



The Zoll R Series BLS Defibrillator includes Guidelines 2005-compatible AED with Real CPR Help, manual override, OneStep system, code-readiness testing system, rectilinear biphasic technology, compact flash card slot, 3 lead CG cable with AHA markings, built-in port, integrated AC Power, (120 VAC/ 60 Hz) and optional parameters.

Warranty: 5 Year Hospital Warranty.

The R Series BLS shows first time responders a simple, one-button AED interface. When the Code Team arrives, a member can simply press a button to turn the BLS device into a full-function manual defibrillator. If pressed, SpO2 becomes functional, and if installed, the pacing function is revealed. This entry _level model allows hospitals with tight budgets to deploy R Series technology. R Series BLS is particularly good for low-acuity area, where advanced capabilities are rarely needed.

R Series is the first device to provide a pediatric electrode with a built-in CPR sensor to help when performing CPR on a child. Because children are not small adults, all the R Series defibrillators feature a pediatric analysis algorithm that is activated when OneStep Pediatric CPR Electrodes are attached.

Features:

CPR Help® special technology -

OneStep™, CPR Stat-padz®, and CPR- D-padz® electrodes with real-time CPR feedback.

Consistent – The R Series defibrillators each use the same uniform operating system, cables, paddles, batteries, internal handles, and electrodes common to all ZOLL manual defibrillators

Adaptable – Mix and match different R- Series products by clicking a button;

Rectilinear Biphasic™ waveform (RBW) technology with superb biphasic waveform;

Audio and Video signalling;

CPR Dashboard™ – Detailed real-time display of CPR quality metrics that uses Real CPR Help® technology;

See-Thru CPR^\circledast – Minimizes pause time during CPR and increases CPR fraction by filtering out CPR artifact;

High-current defibrillation – Delivers optimal treatment for all of your patients





Zoll R Series Plus

The Zoll R Series Plus Defibrillator with Expansion Pack combines the simplicity of the BLS R Series Defibrillator and can transform into an ALS Defibrillator for advanced life support.

Features:

- Real CPR Help.
- See-Thru CPR filter and compression index.
- OneStep Electrode Technology.
- ECG 3-lead cable with AHA markings.
- OneStep system with CPR cable.
- Code readiness testing system that self-tests over 100 parameters.
- Flexibility to transform from BLS to ALS.
- Integrated AC power (120 VAC / 60 Hz).
- Built-in test, compact flash, and USB port.
- WiFi (802.11) compatible (*requires modem).



Zoll AED Plus Demo Kit

Zoll AED Plus Demo Kit

- Zoll carry bag
- Manikin torso with head
- One CPR-Demo Pad
- Simulator
- Velcro strips to attach pads to manikin, and one "Y" cable with simulator connector

*The demo kit cannot be used with the Zoll AED Plus Trainer, but only with the AED Plus Simulator and live Zoll AED Plus.



Honeywell Fenzy / Fire Rescue



Fenzy (EEBD)

Fenzy Bioscape 15mins EEBD C/W 3L 200BAR Steel Cylinder, Honeywell (Part of National CERT Equipment Supply)

Light, compact and easy to use, our Emergency Escape Breathing Apparatus (EEBA) are perfectly adopted to confined spaces, marine, industrial and Oil & Gas applications. They are available with duration of 10 or 15 minutes.

Key Features:

- Light and compact
- 10 to 20 mn autonomy depending on the model
- Alarm whistle positioned next to the ear
- Steel and composite cylinders available



Honeywell EN T8000 SCBA

Sperian's new series of SCBAs certified by EN standard — the T8000 EN SCBA. It strictly passed 1.2 million continuous breathing tests & provides high reliability & stability.

Includes:

- EN 137-2006 certified SCBA.
- Pano Mask
- Passed 1.2 continuous breathing tests, provides high reliability & stability.
- Light weight, total weight only 10.4g (including 3.8 Kg cylinder), suitable for long time wearing.
- High technology reducer design, simple & stable, easy to maintain.
- High efficiency rescue outlet provides high air flow for rescue purpose.
- Built in High Pressure hose with exposure hole outside, ensures user safety.
- Chest whistle provides over 90dB alarm.
- Flexible Banjo connector provides more flexibility when wearing the demand valve.
- Carbon Fiber Composite 6.8L Cylinder
- Type 1 SCBA



Honeywell Fenzy / Fire Rescue



Fenzy Aeris Comfort SCBA (Type 2 SCBA)

Self Contained Breathing Apparatus designed for shipping, where such devices are mandatory. It is a user- friendly apparatus allowing a safe and comfortable breathing. Compliant with the most recent MED, SOLAS and AS/NZS 1716 standards.

Lite Force Helmet



Lite Force Helmet HT-LF2-HDO

Lite Force Plus Modern helmet for structural fire fighting operations. Provides advanced FYR-glass shell technology. Improved internal components. Good fit and ride. Full choice of NFPA 1971, 2007 edition and/or OSHA compliant eye protection system. Ear covers: yellow Nomex®/FR cotton.

Certification: NFPA 1971

Honeywell Wristlet Gloves



Honeywell Wristlet Gloves Model GL-7500mk

An economic double chromium-tanned suede leather that meets the thermal and duribility requirements of NFPA 1971.

Certification: NFPA 1971

Ranger™ Series Boots



Ranger™ Series Boots Model 1600

Insulated lightweight model with wool felt lining. Roomy steel toe provides extra comfort, and steel bottom plates and shanks offer unmatched impact/ compression and puncture protection.

Certification: NFPA



Honeywell Fenzy / Fire Rescue

FE2000 Turnout Gear



Honeywell FE2000 Turnout Gear

Outer Shell: Nomex Delta T 75% Nomex (Meta Aramid), 23% Kevlar (Para Aramid) and 2% P-140(Carbon Fiber) 220 +/-11 g/m2. **Moisture Barrier:** Stedair 3000e®- Aramid spunlace laminated to breathable PTFE membrane.

135±15g/m2

Thermal Barrier: Meta/Para-Aramid felt quilted to 50% Nomex 50%

FR- Viscose woven fabric

Certification: EN469-2005, incorporating amendment A1:2006;

XFRPAC00006 Turnout Gear



MorningPride® RANGER™ Ranger-XFRPAC00006 Turnout Gear

Tough, rugged, made to fit each unique firefighter, RANGER™ turnout gear protects through the roughest of calls. Offering you a wide variety of options so you can custom design your gear to serve your specific needs, RANGER™ gear is comfortable and light, making it the optimal choice for budget-conscious fire departments who do not want to compromise on quality or protection.

Certification: NFPA 1971

VE-XFRPAC00008 Turnout Gear



MorningPride® VE Gear VE-XFRPAC00008 Turnout Gear

VE Gear was developed to deliver value-engineered turnout gear fully certified to NFPA standards, at a price that meets the needs of more budget- restrained departments. It offers two closure styles, both fully equipped with the necessary options to ensure safe and functional performance. With VE Gear you know you are getting tough, reliable gear that will not compromise protection.

Certification: NFPA 1971





Fendall Porta Stream

Model Number: Porta Stream I

Solution: Versatile flushing fluid options include Sperian

Saline concentrate, Sperian Water Additive,

1 gallon container of Sperian Saline solution Flow Duration: 6

minutes

Dimension: 15 1/2" L x 22 1/2" H x 13 1/2" D

Capacity: 6 Gallons

Maintenance: Replace Sperian Saline solution every 6 months, replace Sperian water additive every 4 months



Porta Stream II

Model Number: Porta Stream II

Solution: Versatile flushing fluid options include Sperian

Saline concentrate, Sperian Water Additive, 1 gallon container of Sperian Saline solution Flow

Duration: 15 minutes

Dimension: 19 3/4" L x 24" H x 19" D

Capacity: Large 16 gallon (60.5L) capacity permits thorough

flushing by providing 0.4 gpm over the entire

15-minute flushing period required by ANSI Z358.1-2004 Maintenance: Replace Sperian Saline solution every 6 months, replace Sperian water additive every 4 months



Eyesaline



Model Number: Eyesaline

Available Sizes: 80z, 160z, 32oz, 70oz, 180oz

Specification: Sealed, sterile, bottles contain Sperian Saline — a buffered, saline solution superior to tap water for emergency eye care. Blow-fill-seal bottle are tamper resistant yet easily removed in an emergency.

Expiration: Bottle have 36 month shelf life from date of manufacturing.

EW6



Model Number: EW6

Material: PE

Size: 21 cm (H.) x 7 cm (W.)

Specification: Provide immediate help for eyes

Usage: Keep filled with sterile water; when your eyes are infected with chemical spray, keep pushing/squeezing the body of bottle to pour the water out into your eyes for

thoroughly, cleaning



Flexovit

Cutting, Grinding, Polishing - BF27

Flexovit "All in 1" benefits:

- · cutting light grinding and polishing with one single product no
- more time loss due to machine or product changes
- the fine grit provides an excellent and uniform finishing result
- extreme long wheel life compared to conventional products low
- vibration; comfortable operation
- · free of iron, Sulphur and chlorine
- very smooth grinding result with an incredible clean surface low
- · cutting temperature due to special filters
- and it's from Flexovit, so no need to question quality



Maximum safety due to 3 layered strong reinforcements



Use the new "All in 1" from Flexovit to cut steel and stainless steel plates tubes and other application quickly, easily and very smoothly. The wheel cuts mostmaterials like many dedicated cutting wheels.



Use the same wheel at a 30° angle for light grinding jobs. The "All in 1" give a nice smooth grinding result and an incredible clean surface. The triple layer reinforcement of this advanced wheel guarantees maximum user safety on grinding jobs.



A 15° working angle offers users of the "All in 1" a third function. The fine Grit together with light pressure provides an excellent and uniform polishing result.

P/N	Size(mm)	Specification	Max R.P.M.	Std. Pack Qty.	Article No.
7210016	100x2.2x16.0	A46S-BF27	15 300	25	66252844087
7211522	115x2.2x22.23	A46S-BF27	13 300	25	
7212522	125x2.2x22.23	A46S-BF27	12 250	25	66252844088



Flexovit

Flexovit Grinding BF-27

Grinding Wheels

A30S I/F A24/30T I/F

- Standard grade for general purpose grinding of Stainless steel and harderferrous metals.
- Free of iron (I/F)
- Excellent grinding performance And stock removal.

P/N	Size(mm)	Specification	Max R.P.M.	Std. PackQty.	Article No.	
6710240	100x4.0x16.0	A30S-BF27 I/F	15 300	50	66252844172	
6710260	100x6.0x16.0	A30S-BF27 I/F	15 300	50	66252844074	
6711560	115x6.0x22.23	A30S-BF27 I/F	13 300	50	66252844132	
6812768	125x6.8x22.23	A24/30T-BF27 I/F	12 250	50	66252844075	
6815268	150x6.8x22.23	A24/30T-BF27 I/F	10 200	25	66252844134	
6817845	180x4.5x22.23	A24/30T-BF27 I/F	8 500	40	66252844174	
6817868	180x6.8x22.23	A24/30T-BF27 I/F	8 500	25	66252844077	
6823068	230x6.8x22.23	A24/30T-BF27 I/F	6 650	10	66252844144	

A24/30T

 General purpose grinding of ferrous metal Welds and structural steels. · Excellent grinding performance and life.

A30V

Long life grade for ferrous metal welds and structural steels

P/N	Size(mm)	Specification	Max R.P.M.	Std. Pack Qty.	Article No.
7917868	180x6.8x22.23	A30V-BF27	8 500	25	66252844086

General purpose grinding of ferrous metal welds and structural steels

 Excellent grinding performance and stock removal.

P/N	Size(mm)	Specification	Max R.P.M.	Std. PackQty.	Article No.	
6010260 6012768 6015268 6017845 6017868 6023068	100x6.0x16.0 125x6.8x22.23 150x6.8x22.23 180x4.5x22.23 180x6.8x22.23 230x6.8x22.23	A24/30T-BF27 A24/30T-BF27 A24/30T-BF27 A24/30T-BF27 A24/30T-BF27 A24/30T-BF27	15 300 12 250 10 200 8 500 8 500 6 650	50 50 25 40 25 10	66252844079 66252844080 66252844133 66252844173 66252844078 66252844177	

Flexovit Cutting BF - 42

A30S I/F A24/30T I/F

Cutting-off Wheels

Standard grade - for cutting stainless steel

Free of iron (I/F)

And ferrous metals • Fast cutting and excellent life suitable for notching

P/N	Size(mm)	Specification	Max R.P.M.	Std. PackQty.	Article No.
6710234	100x3.4x16.0	A30S-BF42 I/F	15 300	100	66252844034
6711534	115x3.4x22.23	A30S-BF42 I/F	13 300	100	
6812734	125x3.4x22.23	A24/30T-BF42 I/F	12 250	100	66252844035
6817834	180x3.4x22.23	A24/30T-BF42 I/F	8 500	50	66252844033
6823034	230x3.4x22.23	A24/30T-BF42 I/F	6 650	20	

A30S A24/301

 General purpose cutting of ferrousetals including structural steel and sheet metals Excellent cutting performance and life Suitable for notching



Flexovit

Technical Information

MARKING SYSTEM OF ABRASIVE CUTTING-OFF & GRINDING WHEELS							
Type of Abrasive A	Grit Size 30		Hardr	ness G S	rade	Type of Bond BF27	
A = Aluminum Oxide C = Silicon Carbide Z = Zirconia Alumina	Coarse Medium 16 30 20 to 24 60	Fine 80 to 100	Soft M N 0 P	edium Q R S	Hard T U V	B = Bakelite / Resinoid bond BF = Bakelite and glass fibre reinforcement	

SHAPE SPECIFICATION SYSTEM					
Bf 27	BF 41	BF 42			
Depressed center grinding wheels, Thickness from 2.2-10mm. Available in diameters 76-230mm for hand-held machines.	flat cutting-off wheels. Available in diameters 76-406mm forhand- held machines and 300-406mm For stationery machines.	Depressed center cutting-off wheels. Available in diameters 76-230mm			
Application: Grinding	Application: cutting-off	Application: Cutting-off			

METAL RING WITH VALIDITY DATE						
V	= validity date (pro	duction quarter-	+3year)			
	V01	V04	V07	V10		
	1st Quarter	2nd Quarter	3rd Quarter	4th Quarter		

Operating Speeds

Flexovit products are designed and tested for certain applications and operating speeds. Choose a wheel suitable for the application material. Suitable materials are indicated on the wheel label. Before mounting the grinding or cutting-off wheel on the machine, Ensure that the operating speed of the machine does not exceed the maximum operating speed as it is marked on the product.

SPEED CONVERSION FOLLOWING EN 12413					
Wheel	Maximum p	eripheral operatir	ng speed in m /s		
diameter					
(mm)	63	80	100		
50/51	24100	30600	38200		
63/65	19100	24300	30250		
76	15850	20150	25150		
80	15100	19100	23900		
85	14200	18000	22500		
100/102	12100	15300	19100		
115	10500	13300	16650		
125	9650	12250	15300		
150/152	8050	10200	12700		
180	6700	8500	10650		
200	6050	7650	9550		
230	5250	6650	8350		
250/254	4850	6150	7650		
300/305	4050	5100	6400		
350/356	3450	4400	5500		
400/406	3050	3850	4800		



TOKA/ BAHCO/NORTON





Toka Cutting 4" Toka Cutting 7" Toka Cutting 12" Toka Cutting 14"

Toka Cutting 14" Toka Cutting 16"

Toka Grinding Depressed Center 4'
Toka Grinding Depressed Center 7'



DSKDiamond Blade Size 4 Made in Japan





Bahco Hacksaw Sandcut 18T Bahco Hacksaw Sandcut 24T Bahco Hacksaw Sanflex 18T Bahco Hacksaw Sanflex 24T









Norton Cut-off 7

(180mm x 2.5mm x 22.23mm)

Norton Cut-off 4

(100mm x 2.5mm x 16mm)

Norton Cut-off 12

(300mm x 3mm x 25.4mm)

Norton Cut-off 14

(350mm x 3mm x 25.4mm)

Norton Cut-off 16

(400mm x 3mm x 25.4mm)

Norton Grinding 4

(100mm x 6mm x 16mm)

Norton Grinding 7

(180mm x 6mm x 22.23mm)



Adhesives & Abrasives





Crocodile Masking Tape
Crocodile Masking Tape
Crocodile Masking Tape
Crocodile Masking Tape

Crocodile Masking Tape Crocodile Masking Tape Crocodile Masking Tape Crocodile Masking Tape

2 1/2" 3/4"



Crocodile Aluminum Duct Tape 2 x 50 Yards Crocodile Aluminum Duct Tape 1 x 50 Yards Crocodile Aluminum Duct Tape 3 x 50 Yards



1/2*

1/4"

1 1/2"

Crocodile Electrical Tape Crocodile Electrical Tape

Blue Green Red White Yellow

Black







Crocodile Sandpaper	#100	Crocodile Sandpaper	#240
Crocodile Sandpaper	#1000	Crocodile Sandpaper	#280
Crocodile Sandpaper	#120	Crocodile Sandpaper	#320
Crocodile Sandpaper	#1200	Crocodile Sandpaper	#360
Crocodile Sandpaper	#150	Crocodile Sandpaper	#400
Crocodile Sandpaper	#1500	Crocodile Sandpaper	#60
Crocodile Sandpaper	#1500	Crocodile Sandpaper	#60
Crocodile Sandpaper	#180	Crocodile Sandpaper	#600
Crocodile Sandpaper	#2000	Crocodile Sandpaper	#80
Crocodile Sandpaper	#220	Crocodile Sandpaper	#800

Crocodile Floor Sanding Grit #100 12 x 50 Meters Crocodile Floor Sanding Grit #120 12 x 50 Meters Crocodile Floor Sanding Grit #240 12 x 50 Meters Crocodile Floor Sanding Grit#36

12 x 50 Meters

Crocodile Floor Sanding Grit #36 24 x 50 Meters Crocodile Floor Sanding Grit #60 12 x 50 Meters Crocodile Floor Sanding Grit #80 12 x 50 Meters



3M Floor Sanding Grit #100 12 x 45.7 meters

 3M Floor Sanding Grit #36
 12 x 45.7 meters

 3M Floor Sanding Grit #36
 12 x 45.7 meters

 3M Floor Sanding Grit #50
 12 x 45.7 meters

 3M Floor Sanding Grit #60
 12 x 45.7 meters

 3M Floor Sanding Grit #80
 12 x 45.7 meters

 3M Floor Sanding Grit #80
 12 x 45.7 meters





WD40/ Spray Paints/ Roller Brush



WD-40 3.0oz	WD-40	Gallon
WD-40 6.5oz	WD-40 Degreaser	360ml
WD-40 9.0oz	WD-40 Dry Lube PTFE	360ml
WD-40 11.2oz	WD-40 White Lithium Greas	se 360ml
WD-40 12.9oz	WD-40 Silicone Lubricant	360ml

WD-40 13.9oz





Spray Paint Gloss Black #39 Spray Paint Black #4 Spray Paint Blue #21 Spray Paint Clear #190 Spray Paint Primer Gray #68 Spray Paint Deep Green #13 Spray Paint Orange #141 Spray Paint Orange Red #14 Spray Paint Signal Red #23 Spray Paint Silver #36 Spray Paint Violet #45 Spray Paint White #40 Spray Paint Yellow #41



Jackson Belt Dressing 160z Jackson Electrical Contact Cleaner 160z Jackson Electronic Contact Cleaner 160z



Hitech Baby Foam Roller	4"
Hitech Paint Roller	7"
Hitech Paint Roller	9"
Hitech Paint Roller Radiator	4"
Hitech Paint Roller Refill	4"
Hitech Paint Roller Refill	7"
Hitech Paint Roller Refill	9"
Hitech Paint Roller Foam Refill	4"
Hitech Paint Roller Foam Refill	7"
Hitech Paint Roller Foam Refill	9"

Globe Paint Brush 3/4"
Globe Paint Brush 3/4"
Globe Paint Brush 1 1/2
Globe Paint Brush 1*
Globe Paint Brush 2"
Globe Paint Brush 2 1/2"
Globe Paint Brush 3 3"
Globe Paint Brush 4"







Drill Bit	3/8"	Drill Bit	19/32"
Drill Bit	5/8"	Drill Bit	41/64"
Drill Bit		Drill Bit	
Drill Bit		Drill Bit	
Drill Bit		Drill Bit	
Drill Bit		Drill Bit	
		Drill Bit	
Drill Bit		Drill Bit	6.0mm
Drill Bit		Drill Bit	
Drill Bit		Drill Bit	
Drill Bit		Drill Bit	
Drill Bit	9/64"	Drill Bit	
Drill Bit	11/16"	Drill Bit	
Drill Bit	11/32"	Drill Bit	
Drill Bit	11/64"	Drill Bit	
Drill Bit	13/32"		10.0mm
Drill Bit			10.5mm
Drill Bit			11.1mm
Drill Bit			11.5mm
Drill Bit			12.0mm
Drill Bit		Drill Bit	12.5mm
וום ווווטו	1//04		



New Items

Picture Description Honeywell Impact Sport Electronic Earmuffs Model: Howard Leight Impact Sport R091526 Color: Hunter Green Style: Folding Material: Plastic NRR: 22dB Features of Howard Leight Impact R-01526 Ear Muffs: Sound amplification allows wearers to hear important communication, alarms/warning signals, co-workers voices Directionally placed stereo microphones amplify and enhance sound for more natural hearing Ideal for hearing impaired workers Limits sound amplification to 82dB Automatic shut-off and AUX signal input New easy-access battery compartment Inclusion: 2 AAA Battery **AUX** Honeywell POLYTRIL Gloves The polytril TM line features seamless and lightweight polyamide liners with nitrile / nitrile foam coating. COMFORT The tight knit gives the glove perfect support, limits the penetration of dirt and offers a good dexterity. Non pilling, the polyamide is suitable for precision work. The ventilated back improves the glove's breathability. RESISTANCE The nitrile coating provides outstanding abrasion resistance and impermeability to oils. **HYGIENE** The black coating makes the gloves more soil proof, thus increasing its last. EN 420-2003 - General requirements EN 388-2003 - Mechanical performances Honeywell SHARPFLEX Gloves The **sharpflex** line features lightweight composite yarn gloves. COMFORT The knitting technique gives the gloves perfect support, limits the penetration of dirt and offers a good touch. The ventilated back improves the glove's breathability. RESISTANCE & SAFETY The composition of the glove offer a constant, reliable and safe protection to high cut risks. Version in textile, latex, nitrile foam and PU. HYGIENE The dark colour insures a longer use. EN 420-2003 - General requirements EN 388-2003 -

Mechanical risks EN 407-2004 - Thermal risks



New Items

Picture Description



Honeywell Vertigo Check & Go Black PU 5 Gloves

Feature

Black Spectra® and composite fiber knitted glove Black Polyurethane coating on palm

Benefit

COMFORT

The knitting technique helps to obtain a glove that conforms snugly to the hand, with good dexterity.

The glove offers maximum comfort and added sturdiness.

The cool Spectra® touch gives an added sensation of comfort.

The tight knit (gauge 13) gives the glove perfect support, limits the penetration of dirt and offers a good touch.

The glove's ventilated back optimizes its breathability.

RESISTANCE

The Spectra®/lycra® thread provides outstanding properties against cuts.

The polyurethane coating at the palm and fingertips provides outstanding abrasion resistance.

The composite fiber fully portected by polyamide increase the cut resistance.

Caution! Do not expose this glove to the heat.

CHARACTERISTICS : Black Spectra® and composite fiber knitted glove

Black Polyurethane coating on palm

Product Technology

Knitted Coated

Fiber

Spectra® and composite fiber

Glove/liner color

Black

Coating Type

PU

Coating Color

Black

Length

23,5 cm

Harmlessness

In conformity with the European standards

Dexterity

Class 5



Picture	Description
	Honeywell Rig Dog™ CR Gloves
	(MPCT2000) The new and improved Honeywell Rig Dog(TM) CR gloves now with cut resistance on the palm and fingers. The Rig Dog gloves features moulded thermoplastic rubber (TPR) patches for impact protection and are ANSI A7 cut-resistant palm to enhance protection against cuts and slashes. The Rig Dog CR all-season MPCT2000 are comfortable and stylish to wear.
	Salisbury Utility Work Glove General Purpose
EALISBURY	(UWG-GPU) This glove features asphalt reinforcement on the palm to resist abrasion. The top of the hand is made out of a stretchable, light weight and breathable reinforced, nylon for comfort. This glove also features internal knuckle protection. All gloves are available in sizes S-2XL Not cut proof, puncture proof or fire retardant. Do not expose near open flames, sparks or arc zones. Salisbury Kevlar Utility Work Glove General
	Salisbury Keviar Otility Work Glove General
	(UWG-KLG)
	KEVLAR® Utility Glove - CUT RESISTANT - ALL PURPOSE Features & Benefits: • This all-purpose work glove is highly cut- resistant and features a 100% KEVLAR® lining. This glove has great dexterity and durability. • All gloves are available in sizes S-XXL. WARNING! • Not Cut Proof, Puncture Proof or Fire Retardant. Do NOT Expose Near Open Flames, Sparks or Arc Zones. • When ordering add suffix: "/S" for Small, "/M" for Medium, "/L" for Large, "/XL" for Extra Large, or "/XXL" for 2X Large.



Picture	Description
	Blue Eagle EW607 Product name: Emergency Eyewash Shower Type Material: 304 Stainless steel Copper alloy shower head. Diameter of shower head: 24cm. Diameter of basin: 30m. Category: emergency Description: • Emergency eye wash and shower • Operation • Valve • Water pressure • Spray heads with protective covers • Copper alloy shower head • Made in Taiwan
	Camel Ordinary Rainboots Material: PVC Specification: Rainboots for general purpose.
	Supertuff Rainboots with Steel Toe Material: PVC Specification: Rainboots with steel toe for general purpose.



Picture	Description
	The Zoll M Series combines a defibrillator, ECG display, advanced monitoring capabilities, and noninvasive transcutaneous pacing (NTP) with communication, data printing and recording capabilities in a single lightweight portable instrument. The M Series has been designed for all resuscitation situations and its small, compact, lightweight design makes it ideal for accompanying patients during transport. It features CPR monitoring by evaluating the rate and depth of chest compressions while providing feedback to the rescuer. When equipped with a PCMCIA card, the Zoll M Series defibrillator records ECG and virtually all device data when the device is turned on. In addition, voice data from any incident around this device can also be recorded. • Manual • Delivers up to 360 joules • into a 50 ohm impedance. • ECG Monitoring with 3 or 5 • lead patient cable. • Up to 2.5 hours of • monitoring on battery • power. • Integrated CPR assistance.

User-friendly temporary ventilation for hospitalized patients The Eagle II™ portable ventilator is the ideal solution for ICUs, emergency departments, and intra- hospital transport of infants (≥5 kg), pediatric patients, and adults. Weighing less than 10 lbs., it can be mounted on the wall or on a roll stand or bed. In addition to AC mode, the Eagle II offers SIMV and CPAP (NPPV/PPV) modes with pressure support. The Eagle II uses Smart Help™ technology to assure patient safety by providing real-time, on-screen prompts that guide clinicians in responding to alarms. It also incorporates Masimo® SET® pulse oximetry, proven clinically superior for continuous, accurate SpO2 and pulse rate readings	Picture	Description
Features: Designed for the ICU, emergency department and intra-hospital transport. Supports infants ≥5kg, pediatric patients, and adults 10-hour battery run-time; rapidly recharges in 2 hours Smart Help™ display MRI conditional system available.	Laster of the Control	User-friendly temporary ventilation for hospitalized patients The Eagle II™ portable ventilator is the ideal solution for ICUs, emergency departments, and intra- hospital transport of infants (≥5 kg), pediatric patients, and adults. Weighing less than 10 lbs., it can be mounted on the wall or on a roll stand or bed. In addition to AC mode, the Eagle II offers SIMV and CPAP (NPPV/PPV) modes with pressure support. The Eagle II uses Smart Help™ technology to assure patient safety by providing real-time, on-screen prompts that guide clinicians in responding to alarms. It also incorporates Masimo® SET® pulse oximetry, proven clinically superior for continuous, accurate SpO2 and pulse rate readings. Features: Designed for the ICU, emergency department and intra-hospital transport. Supports infants ≥5kg, pediatric patients, and adults 10-hour battery run-time; rapidly recharges in 2 hours Smart Help™ display MRI

New Items



Crocodile Cloth Duct tape

-Cloth tape is an adhesive tape made with a cloth backing to make it durable and flexible. The tape is useful for various purposes such as bandages, sealing walls, electrical and plumbing tasks.

Colors:

- Silver
- Blue
- Beige
- Black
- Green
- WhiteYellow
- Red

Size:



Silicon Sealant Siltite

-Sealant is a substance used to block the passage of fluids through the surface or joints or openings in materials, a type of mechanical seal. In building construction sealant is sometimes synonymous with caulking and also serve the purposes of blocking dust, sound and heat transmission.